



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 1 / 13

EN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: PFP370
Product name: FABER 30 2.0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: ALKALINE DEGREASING DETERGENT

1.3. Details of the supplier of the safety data sheet

Name: FABER CHIMICA S.R.L.
Full address: Via Ceresani 10
District and Country: 60044 Campo D'Olmo - Fabriano (ANCONA) ITALIA
Tel.: 0732627178
Fax: 073222395
e-mail address of the competent person responsible for the Safety Data Sheet: quality@fabersurfacecare.com

1.4. Emergency telephone number

For urgent inquiries refer to:

Belgium
BELGISCH ANTIGIFCENTRUM
Bel gratis 070 245 245
8002 5500, vanuit Groothertogdom Luxemburg
We beantwoorden je oproep, elke dag, 24 op 24 uur

Croatia
Ksaverska cesta 2, 10000 Zagreb
T 01 2348 342
Voditeljica: dr. sc. Željka Babić

Denmark
Bispebjerg Hospital
Bispebjerg Bakke 23E, opgang 20 C
2400 Kbh NV
T 8212 1212

Estonia
Poison information telephone number (Mürgistusteabekeskuse number) is nationally 16662, calling from abroad (+372) 7943 794
Hotline 16662 of the Poisoning Information Centre is active 24/7.
National poison information centre service in Estonia is accessible at www.16662.ee
There are no limitations to users

Iceland
Eitrunarmiðstöð
543 2222
112
543 1000

Ireland
National Poisons Information Centre
Beaumont Hospital, Beaumont, Dublin 9., Ireland
+353 1 809 2166
E-mail chemicalsinfo@beaumont.ie

Latvia
Valsts ugunsdzēsības un glābšanas dienests, phone number: 112. Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs, Hipokrāta 2, Rīga, Latvija, LV-1038, phone number +371 67042473. Service is available 24 hours.

Lithuania
APNUODYJIMŲ CENTRAS
+370 (85) 2362052

Malta

Malta Competition and Consumer Affairs Authority (MCCAA)
Mizzi House, National Road, Blata I-Bajda HMR9010, Malta
Phone +356 2395 2000
E-mail info@mccaa.org.mt
Norway
Kontakt Giftinformasjonen hvis uhellet er ute
22 59 13 00
Døgnåpen telefon.
Sweden
112 – ask for Poisons Information" (in Swedish this will be: "112 – begär
Giftinformation")

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2

H319

Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

H319

Causes serious eye irritation.

Precautionary statements:

P264

Wash hands and face thoroughly after handling.

P280

Wear eye protection / face protection.

P337+P313

If eye irritation persists: Get medical advice / attention.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 3 / 13

EN

SECTION 3. Composition/information on ingredients ... / >>

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Sodium silicate		
INDEX	$5 \leq x < 6$	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	215-687-4	
CAS	1344-09-8	
REACH Reg.	01-2119448725-31	
Sodium (xylenes and 4-ethylbenzene)sulfonates		
INDEX	$1 \leq x < 1,5$	Eye Irrit. 2 H319
EC	701-037-1	
CAS	1300-72-7	
REACH Reg.	01-2119513350-56	
tetrasodium ethylenediaminetetraacetate		
INDEX	$1 \leq x < 1,5$	Acute Tox. 4 H302, Acute Tox. 4 H332, STOT RE 2 H373, Eye Dam. 1 H318
EC	200-573-9	LD50 Oral: 1780 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l
CAS	64-02-8	
REACH Reg.	01-2119486762-27	
Alcohols, C13-15, branched and linear, ethoxylated, in water		
INDEX	$1 \leq x < 1,5$	Acute Tox. 4 H332, Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC		ATE Inhalation mists/powders: 1,5 mg/l, ATE Inhalation vapours: 11 mg/l
CAS	157627-86-6	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 4 / 13

EN

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 5 / 13

EN

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU Deutschland Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur
Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
TLV-ACGIH ACGIH 2023

tetrasodium ethylenediaminetetraacetate

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
		mg/m3	ppm	
AGW	DEU	110	20	

Predicted no-effect concentration - PNEC

Normal value in fresh water	2,83	mg/l
Normal value in marine water	0,283	mg/l
Normal value of STP microorganisms	50	mg/l
Normal value for the terrestrial compartment	1,1	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic
	local	systemic	local	systemic	local	systemic	local
Oral				25			
				mg/kg bw/d			
Inhalation	1,2		0,6		3	3	1,5
	mg/m3		mg/m3		mg/m3	mg/m3	mg/m3

Sodium silicate

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
		mg/m3	ppm	
TLV-ACGIH		2		

Predicted no-effect concentration - PNEC

Normal value in fresh water	7,5	mg/l
Normal value in marine water	1	mg/l
Normal value for water, intermittent release	7,5	mg/l
Normal value of STP microorganisms	348	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic
	local	systemic	local	systemic	local	systemic	local
Oral				0,8			
				mg/kg/d			
Inhalation				1,38			5,61
				mg/m3			mg/m3
Skin				0,8			1,59
				mg/kg/d			mg/kg/d



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 6 / 13

EN

SECTION 8. Exposure controls/personal protection ... / >>

Sodium (xylenes and 4-ethylbenzene)sulfonates

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,23	mg/l
Normal value in marine water	0,023	mg/l
Normal value for fresh water sediment	0,862	mg/kg/d
Normal value for marine water sediment	0,0862	mg/kg/d
Normal value for water, intermittent release	2,3	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,037	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				3,8 mg/kg bw/d				
Inhalation				6.6 mg/m3				26.9 mg/m3
Skin			3.8 mg/kg bw/d	68,1 mg/kg bw/d			0.096 mg/cm2	136.25 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	Amber	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not flammable	
Lower explosive limit	not available	



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 7 / 13

EN

SECTION 9. Physical and chemical properties ... / >>

Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	11-11,4	Concentration: 5 %
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1030-1050 g/l	Temperature: 5 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 5,78 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Sodium silicate

May react with: aluminium,zinc,tin

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

Sodium silicate

Stable in normal conditions of use and storage

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

Sodium silicate

May react violently with: strong acids

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Sodium silicate

Keep away from: acids

10.6. Hazardous decomposition products

Sodium silicate

May develop: carbon oxides

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 8 / 13

EN

SECTION 11. Toxicological information ... / >>

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

tetrasodium ethylenediaminetetraacetate	
LD50 (Dermal):	> 8,5 g/kg bw rabbit
LD50 (Oral):	1780 mg/kg rat

Sodium silicate	
LD50 (Dermal):	> 5000 mg/kg rat
LD50 (Oral):	3400 mg/kg rat

Alcohols, C13-15, branched and linear, ethoxylated, in water	
LD50 (Oral):	> 300 mg/kg ratto

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 9 / 13

EN

SECTION 11. Toxicological information ... / >>

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

tetrasodium ethylenediaminetetraacetate	
LC50 - for Fish	2340 mg/l/96h
EC50 - for Algae / Aquatic Plants	8 mg/l/72h
EC10 for Algae / Aquatic Plants	51 mg/l/10d
Chronic NOEC for Algae / Aquatic Plants	484 mg/l
Sodium silicate	
LC50 - for Fish	1108 mg/l/96h Brachydanio rerio
EC50 - for Algae / Aquatic Plants	> 345,4 mg/l/72h Scenedesmus subspicatus
Sodium (xylenes and 4-ethylbenzene)sulfonates	
LC50 - for Fish	1000 mg/l/96h
EC50 - for Crustacea	1000 mg/l/48h Daphnia
Alcohols, C13-15, branched and linear, ethoxylated, in water	
LC50 - for Fish	> 1 mg/l/96h Brachydanio rerio
EC50 - for Crustacea	> 1 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h Scenedesmus subspicatus
Chronic NOEC for Crustacea	> 1 mg/l Daphnia magna

12.2. Persistence and degradability

tetrasodium ethylenediaminetetraacetate	
NOT rapidly degradable	
Sodium silicate	
Rapidly degradable	
Sodium (xylenes and 4-ethylbenzene)sulfonates	
Solubility in water	664000 mg/l 20°C
Alcohols, C13-15, branched and linear, ethoxylated, in water	
Rapidly degradable	

12.3. Bioaccumulative potential

tetrasodium ethylenediaminetetraacetate	
BCF	1,8 Lepomis macrochirus
Sodium (xylenes and 4-ethylbenzene)sulfonates	
Partition coefficient: n-octanol/water	< 3,12 Log Kow 20°C

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 10 / 13

EN

SECTION 12. Ecological information ... / >>

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 11 / 13

EN

SECTION 15. Regulatory information ... / >>

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level



FABER CHIMICA S.R.L.

PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 12 / 13

EN

SECTION 16. Other information ... / >>

- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.



FABER CHIMICA S.R.L.	PFP370 - FABER 30 2.0

Revision nr.1
Dated 02/12/2024
First compilation
Printed on 02/12/2024
Page n. 13 / 13

EN

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.