



FLAGSTONE FIX
STONE CARE EXPERTS



Technical Data Sheet (TDS)

FS GLOSSER PLUS X

Gloss-enhancing stain-resistant protection for natural stone

DESCRIPTION

FS GLOSSER PLUS X is a ready-to-use, solvent-based, satin-finish stone sealer formulated with high-quality acrylic resins to impregnate natural and artificial stones. It enhances surface colour and imparts a rich, wet, and glossy look while offering excellent resistance to oil, water, and stains. Non-yellowing and breathable, it penetrates easily and is ideal for both indoor and outdoor use on granite, silicate-based stones, lime-based stones, and dark-colored stones.

KEY FEATURES

- Intensifies surface coloration
- Delivers a wet-look finish
- Resists yellowing
- Penetrates with ease
- Provides stain resistance
- Repels oil and water
- Maintains surface breathability

APPLICATION AREAS

- Indoor/outdoor
- Granite
- Silicate-based stones
- Lime-based stones
- Dark colored stones

COVERAGE ESTIMATES

Provides coverage of approximately 15 – 35 m² per liter, depending on the porosity of the surface being treated.

STORAGE AND SHELF LIFE

FS GLOSSER PLUS X has a shelf life of approximately 2 years when stored in the original container in a cool and dry place.

APPLICATION GUIDELINES

Surface preparation:

- Ensure the surface is clear of dirt, debris, oil, and any loose particles.
- Remove any existing wax, epoxy, or other coatings prior to application.

- Wash and thoroughly dry the surface to eliminate salts (nitrates, sulfates, chlorides) that can hinder porosity and lead to incomplete impregnation (ask about specialty natural stone cleaners).
- Shield adjacent areas not intended for treatment, as solvent-based products may leave marks.

Application Method:

- It is strongly recommended to conduct a patch test to assess any changes in surface appearance and verify the impregnation's performance.
- Apply FS GLOSSER PLUS X with a fully loaded brush, roller, or mop, making sure the entire surface is thoroughly wetted.
- Allow the product to dry for 10-60 minutes, depending on temperature; reapply on highly absorbent areas as needed.
- Maintain adequate ventilation throughout the application process.
- Allow 48-72 hours for full curing, depending on temperature, humidity, and other environmental factors.
- During curing, protect the surface from direct sunlight and water exposure.

TECHNICAL SPECIFICATIONS

Appearance	Mostly clear liquid
Odor	Mild
Density	0.85 ± 0.1 g/cm ³

CAUTION

- Always wear appropriate protective equipment throughout the application process.
- FS GLOSSER PLUS X does not offer protection against strong acids.
- Severely deteriorated surfaces must be resurfaced before application.

FLAGSTONE FIX
Zyax Chem PVT. LTD.

Third Floor, Kamer Building, 38, Cawasji Patel Street, Fort, Mumbai, Maharashtra, 400001, India.

☎ +91-8779-240-420

✉ info@zyax.in

🌐 www.flagstonefix.com